



***i-tec***

**AUTOMATIC  
WATER  
FILTER**



## FEATURES AND BENEFITS (Autotrol 263 Series Control Valve)



- Time-tested Duraflow flapper provides frictionless sealing for longer service life
- Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant
- Optical sensor for precision cycle positioning
- Fully adjustable 5 or 8 cycle control for efficient and reliable water treatment system
- Continuous service flow rate of 25 GPM with a backwash of 20 GPM
- Backwash capability accommodates filter tanks up to 10" and filter up to 22" in diameter
- Super capacitor for keeping time of day during power outage
- Environmental protective cover for water resistance, corrosion resistance, and UV stability
- Programming stored in memory and will not be lost due to power outages
- History data for valve performance.

### MULTI MEDIA SAND FILTER

MODEL	FLOWRATE CU.M/HR		GRAVEL		FINE SAND		GARNET SAND		COARSE SAND		ANTHRACITE	
	MIN	MAX	litres	DEPT INCHES	litres	DEPT INCHES	litres	DEPT INCHES	litres	DEPT INCHES	litres	DEPT INCHES
XM1054	0.80	1.5	5.6	4.0	5.6	6.0	8.5	6.0	8.5	4.0	24.7	18.0
XM1252	1.20	2.1	8.5	4.0	8.5	6.0	11.3	6.0	11.3	4.0	32.0	16.0
XM1354	1.40	2.5	8.5	4.0	8.5	6.0	14.1	6.0	14.1	4.0	41.8	18.0
XM1465	1.60	3.0	11.3	4.0	11.3	6.0	14.1	6.0	19.8	4.0	58.2	24.0
XM1665	2.00	4.0	14.1	4.0	14.1	6.0	19.8	6.0	25.4	4.0	76.0	24.0
XM2260	3.50	6.5	22.6	4.0	22.6	6.0	33.9	6.0	45.3	4.0	122.7	21.0

#### CONDITION FOR OPERATION

1. INLET PRESSURE 25 PSI MIN.



Reg. No. 56Q12409

**Imeltech Sdn Bhd** (223078-K)

136 & 137, Jln KIP 8, Tmn Perindustrian KIP, 52200 Kuala Lumpur, Malaysia.

Tel. +603 6276 7112, 6276 8112 Fax. +603 6274 2112

e-mail: [imeltech@gmail.com](mailto:imeltech@gmail.com) <http://www.imeltech.com>