



i-tec

AUTOMATIC WATER SOFTENER



Reg. No. 56Q12409

FEATURES AND BENEFITS (Autotrol 268 Series Control Valve)



- Time-tested Duraflow flapper provides frictionless sealing for longer service life
- Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant
- Optical sensor for precision cycle positioning
- Designed with double backwash for reduced hardness leakage
- Fully adjustable 5 or 8 cycle control for efficient and reliable water treatment system
- Continuous service flow rate of 25 GPM with a backwash of 20 GPM
- Backwash capability accommodates softener tanks up to 16" and filter up to 18" in diameter
- Super capacitor for keeping time of day during power outage
- Environmental protective cover for water resistance, corrosion resistance, and UV stability
- Soft water refill for a cleaner brine tank
- Programming stored in memory and will not be lost due to power outages
- History data for valve performance

AUTOMATIC WATER SOFTENER

MODEL	FLOWRATE SERVICEMAX CU. M./HR.	FIBRE GLASS TANK INCHES		VOLUME RESIN LITRES	SALT USED PER REGEN KGS.	*BRINE TANK CAPACITY IMP GALLONS	MAX. EXCHANGE CAPACITY CU. M. AT 30 PPM HARDNESS
		DIA	HT				
XS 1054	1.6	10	54	40	7.7	25 (5.4)	72.8
XS 1354	2.8	13	54	70	13.5	25 (9.5)	127.3
XS 1465	4.0	14	65	100	19.3	25 (13.6)	181.9
XS 1665	4.8	16	65	120	23.1	25 (16.3)	218.3
XS 2160	8.0	21	60	200	38.5	45 (27.1)	363.8

* IN BRACKET - ACTUAL BRINE CONSUMPTION PER REGENERATION

CONDITION FOR OPERATION

1. INLET PRESSURE 25 PSI MIN.

QUALITY

1. TREATED WATER QUALITY IS BELOW 2 PPM.

Imeltech Sdn Bhd (223078-K)

136 & 137, Jln KIP 8. Tmn Perindustrian KIP, 52200 Kuala Lumpur, Malaysia.
Tel. +603 6276 7112, 6276 8112 Fax. +603 6274 2112

e-mail: imeltech@gmail.com <http://www.imeltech.com>