



i-tec

**AUTOMATIC
ACTIVATED
CARBON
FILTER**



FEATURES AND BENEFITS
(Autotrol 263 Series Control Valve)



- Time-tested Duraflow flapper provides frictionless sealing for longer service life
- Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant
- Optical sensor for precision cycle positioning
- Fully adjustable 5 or 8 cycle control for efficient and reliable water treatment system
- Continuous service flow rate of 25 GPM with a backwash of 20 GPM
- Backwash capability accommodates filter tanks up to 10" and filter up to 24" in diameter
- Super capacitor for keeping time of day during power outage
- Environmental protective cover for water resistance, corrosion resistance, and UV stability
- Programming stored in memory and will not be lost due to power outages
- History data for valve performance.

ACTIVATED CARBON FILTER

MODEL	SFC TANK DIMENSION		INLET / OUTLET PIPE SIZE		MAX. FILTER FLOW LITRES/HR	ACTIVATED CARBON VOLUME LITRES	WASHWATER FLOW LITRES/HR
	DIA	HT	INCHES	mm			
	INCHES	INCHES					
XA 1054	10	54	1	25.4	2500	40	2500
XA 1252	12	52	1	25.4	2800	50	3000
XA 1354	13	54	1	25.4	3500	65	3500
XA 1465	14	65	1 1/4	31.8	5000	100	5000
XA 1665	16	65	1 1/4	31.8	6000	120	6000
XA 2260	22	60	1 1/4	31.8	7500	200	7500
XA 2460	24	60	1 1/2	38	9500	250	9500

CONDITION FOR OPERATION

1. INLET PRESSURE 25 PSI MIN.



Reg. No. 56Q12409

Imeltech Sdn Bhd (223078-K)

136 & 137, Jln KIP 8, Tmn Perindustrian KIP, 52200 Kuala Lumpur, Malaysia.

Tel. +603 6276 7112, 6276 8112 Fax. +603 6274 2112

e-mail: imeltech@gmail.com <http://www.imeltech.com>